

HOONVED

CE Series

Undercounter glasswashers and dishwashers








The new CE Series has shed its skin... and its heart too!

The flexible line of Hoonved chooses to be even more versatile, including two models in double skin execution, responding to the multiple and varied needs and requirements of the food service sector, ensuring greater energy efficiency and thermal and acoustic insulation. This allows also stand-alone units to guarantee the same results, in terms of noise reduction and heat loss of integrated models.

The washing system of the new CE Series has changed too: upper and lower wash and rinse arms, in stainless steel, which guarantee impeccable washing results and consistently reduced rinse water consumptions.

Performance

-  Up to 1,500 glasses/h
-  Up to 540 dishes/h
-  4 single skin models: CE 43 - CE 46 - CE53 - CE 60
-  2 double skin models: CE 46 DP - CE 60 DP
-  4 washing cycles



Technical specifications

Model	CE 43	CE 46	CE 53	CE 60	CE 46 DP	CE 60 DP
Dimension	mm 430x525x675 h	mm 460x525x675 h	mm 530x605x755 h	mm 460x525x820 h	mm 480x530x705 h	mm 600x620x830 h
Cycle	120-180-240-480 sec	120-180-240-480 sec	120-180-240-480 sec	120-180-240-480 sec	120/180/240/480 sec	120/180/240/480 sec
H door clearance	280 mm	280 mm	280 mm	350 mm	270 mm	330 mm
Rack	350 x 350 mm - Ø 350 mm	400 x 400 mm - Ø 400 mm	450 x 450 mm	500 x 500 mm	400x400 mm Ø 400 mm	500x500 mm
Construction	Single wall	Single wall	Single wall	Single wall	Double wall	Double wall
Machine interior	Self-cleaning	Self-cleaning	Self-cleaning	Self-cleaning	Self-cleaning	Self-cleaning
Rinse-aid pump	Standard	Standard	Standard	Standard	Self-cleaning	Self-cleaning
Wash pump	260 W	260 W	450 W	450 W	Standard	Standard
Drain pump	Optional	Optional	Optional	Optional	350 W	750 W
Peristaltic detergent pump	Optional	Optional	Optional	Optional	On request	On request
Break Tank System	-	-	-	Optional	On request	On request
Electrical connection	230V 50Hz	230V 50Hz	Multipower	Multipower	230 V 1.50 HZ	400 V 3N 50HZ
Total power	3060 W	3060 W	5450 W (7450 W)	5450 W (7450 W)	3150 W	4750 W
Boiler heater	2800 W	2800 W	5000 W (7000 W)	5000 W (7000 W)	2800 W	4000 W
Tank heater	2000 W	2000 W	2000 W	2000 W	2000 W	2000 W
Tank capacity	12 l	12 l	17 l	21 l	12,5 l	20 l
Boiler capacity	4 l	4 l	7,5 l	7,5 l	6 l	7,5 l
Water supply	2÷4 bar Ø 3/4 "G	2÷4 bar Ø 3/4 "G	2÷4 bar Ø 3/4 "G	2÷4 bar Ø 3/4 "G	2÷4 bar Ø 3/4" G	2÷4 bar Ø 3/4" G
Water consumption cycle	2 l	2 l	3,5 l	3,5 l	2 l	3,5 l
Drain hose connection	Ø 28 mm	Ø 28 mm	Ø 31 mm	Ø 31 mm	Ø 28 mm	Ø 31 mm
Acoustic pressure level	< 70 db (A)	< 70 db (A)	< 70 db (A)	< 70 db (A)	63db (A)	63db (A)