

All The Best From **One Supplier**

ART

• SALES • SERVICE • SPARE PARTS •

0 F

MIXER

P

9-ON

MIXING

I

START EVO SPIRAL MIXER WITH FIXED BOWL

STANDARD FEATURES

- Painted steel rack raised from the ground on 4 adjustable feet.
- Bowl, spiral, contrast column and guard made of stainless steel.
- A two-speed motor for spiral and bowl.
- Movement is transmitted by pulleys and V-belts.
- Bowl thrust roller.
- Frontal control with two timers.
- Setting of work time with automatic shift from 1st to 2nd speed.

CAPACITY (kg) •35 •50 •60 •80 •120 •160

TECHNICAL DATA

MODEL			START 35	START 50	START 60	START 80	START 120	START 160
Dough capacity (min./max) *		kg	8/35	8/50	15/60	15/80	20/120	20/160
Flour capacity (min./max) *		kg	5/22	5/30	9/38	9/50	12/75	12/100
Water capacity (min./max) *		lt	3/13	3/20	6/22	6/30	8/45	8/60
Bowl volume		lt	50	75	100	120	205	240
% water/flour minimum		%	55	55	55	55	55	55
Spiral turns 1st / 2nd speed (50/60Hz)		rpm	95	95	93	93	92	92
Bowl turns 1st / 2nd spe <mark>ed (50/60Hz</mark>)		rpm	8.5/189	8.5/189	9/184	9/184	9/183	9/183
Motor power 1st/2nd speed		kw	0.8/1.6	0.8/1.6	1,5/3	1.5/3	3/5.2	3/5.2
Current drawn V 230/400		Α	7.2/4.2	7.2/4.2	11.5/6.5	11.5/6.5	19.5/11.5	19.5/11.5
Spiral bar diameter		mm	28	28	30	30	40	40
Height from bowl edge	A	mm	615	650	780	790	840	900
Total depth	Р	mm	875	945	1030	1100	1240	1240
Total width	L	mm	550	565	645	700	845	845
Height	Н	mm	1100 he	Bakery 1700 jpme	ent Sp 1250 alist	1250	1390	1390
Net weight	12/1/2	kg	170	190	255	260	395	400
* capacity based on the percentage of liquid/flour = 6	0%							

7 21

*: capacity based on the percentage of liquid/flour = 60%

All data are to be considered as nominal, MIXER srl reserves the right to make any changes to the product and/or technical specifications without notice.