

All The Best

From One Supplier

SALES • SERVICE • SPARE PARTS •





ERGO 60

White, powder coated/ Stainless steel/ Marine version

ERGONOMIC HANDLING

Separate removal of bowl and tools. The taller frame allows you to lower the bowl below the tool, so each of them can be removed separately, increasing efficiency.

STAINLESS STEEL CONTROL PANEL Choose between variable speed control, fixed speeds or up to 20 programs with your own programs. All operations are controlled from the intuitive control panel with responsive piezo push button technology. The panel is easy to clean and is dustproof and waterproof.

REMOVABLE SAFETY GUARD

The removable safety guard is made of stainless steel and is easy to remove and dishwasher safe.

ERGONOMIC WORKING HEIGHT

All work at Varimixer ERGO is done with a straight back. There is unhindered access to changing tools at the correct ergonomic working height.

ONE MACHINE - MULTIPLE CAPACITIES

The ERGO60 is also available with a bowl and tools for 30-litre production. The option of producing reduced quantities makes the large machines more versatile.

AUTOMATIC BOWL LOWERING

It is not necessary to watch the mixing process. When the time is up, the control system lowers the bowl, so the tools can drip off directly into the bowl.

LIFT FOR EASY HANDLING

Even the largest bowls can be easily and ergonomically lifted using an electronic bowl lift, which also ensures correct working height during filling and emptying. Choose from several models - or choose a manual bowl trolley for transport only.

HYGIENIC AND EASY TO CLEAN

All surfaces and accessories are made of stainless steel, and the design ensures the best possible hygiene and very easy cleaning. Varimixer ERGO can be washed in accordance with the IP53 standard, and can be upgraded to IP54, with a waterproof stainless steel planetary head.

NO HEAVY LIFTING

The bowl is wheeled into place between the two bowl arms. The bowl is automatically centered and locked into position, when raised.





Waterproof planetary head, stainless steel, IP54



Double chimney, stainless steel, IP54

OPTIONS - SAFETY GUARDS

Removable safety guard in stainless steel. CE-certified



Removable splash guard in stainless steel. CE-certified



All The Best

From One Supplier

• SALES • SERVICE • SPARE PARTS •

VARIMIXER ERGO 60 STANDARD TOOLS - A-EQUIPMENT 60L



Whip, hook, beater and bowl 60 liter in stainless steel.

VARIMIXER ERGO 60 STANDARD TOOLS - B-EQUIPMENT 60/30L



Whip, hook, beater and bowl 60/30 liter in stainless steel.

OPTION - TOOLS



Wing whip, stainless steel



Whip with thinner wires, stainless steel



Whip with reinforcement



Powder mixer, stainless steel



Automatic scraper, stainless steel. Nylon or teflon blade. 60L and 60/30L.



Tool rack, 127 cm



Bowl with bottom draining pipe, stainless steel

EQUIPMENT - TRANSPORTION



Bowl truck



Easylift 30-60



Flexiift Inox



Wheels for bowl



All The Best

From One Supplier

• SALES • SERVICE • SPARE PARTS •



VARIMIXER ERGO 60 MARINE VERSION

Stainless steel execution, water cover at air ventilation, slottet free screws, full welded stainless steel knees, gasket at the rear plate, gasket at front panel and top cover. Complies with USPHS.

Voltage: 3 ph, 440V, 50 Hz with ground. 3.000 W 3 ph, 480V, 50 Hz with ground. 3.000 W


VARIMIXER ERGO 60 STANDARD
White powder coated
1 bowl 60 liter in stainless steel
1 beater in stainless steel
1 hook in stainless steel
1 whip with stainless steel wires
Removable safety guard in stainless steel - CE-certified
Separate removal of bowl and tool
Digital timer and emergency stop
Voltage: 3 ph, 400V, 50 Hz with ground. 3.000 W


CAPACITIES	
Egg Whites	9.0
Whipped cream	15 I
Mayonnaise	48 I
Herb butter	45 kg
Mashed potatoes	36 kg
Bread dough (50% AR)	34 kg
Bread dough (60% AR)	44 kg
Ciabatta dough (70% AR)	40 kg
Muffins	33 kg
Layer cake base	15 kg
Meatball mix	45 kg
Icing	40 kg
Doughnut (50% AR)	36 kg

VARIMIXER ERGO 60 STANDARD TECHNICAL DATA

VARIMIXER ERGO 60 STANDARD TECHNICAL DATA		
Volume	60 1	
Effect	3.000 W	
Standard voltage*	400 V	
Residual current devices (RCD): Industrial environment Light industry/domestic	HPFI type A-SI or PFI type B HPFI type A-SI	
Net weight	330 kg	
HxWxL	1829 x 757 x 1032 mm	
Variable speed	53 – 288 RPM	
Phases	3 ph	
IP code	IP53	
IP code upgrade package	IP54	

*Other voltage power supply <mark>are available upon re</mark>quest in the range of 100 to 480 V. All standard and marine mixers are available in 50 and 60 Hz.





The Bakery Equipment Specialist

12 Tagore Lane Singapore 787474 Tel: +65 64547277 Fax: +65 64587701 Email: info@femac.com.sg