



HOSHIZAKI

UNDERCOUNTER REFRIGERATOR DEPTH 750mm TYPE SERIES



RTC - 120SDA
RTC - 150SDA
RTC - 180SDA

REFRIGERATOR
Depth 750mm type

RTC - 180SDA

RTC - 150SDA

RTC - 120SDA

SPECIFICATION

MODEL NAME	RTC-120SDA	RTC-150SDA	RTC-180SDA
AC SUPPLY VOLTAGE	1/220-240V/50Hz	1/220-240V/50Hz	1/220 - 240V/50Hz
AMPERAGE	1.2A	1.5A	1.7A
STARTING AMPERAGE	6.8A	8.2A	8.2A
ELECTRIC CONSUMPTION(Refrigeration)	193W / 659 BTU	271W / 925 BTU	314W / 1071 BTU
OUTSIDE DIMENSIONS(W x D x H)	1200 x 750 x 800(800-830)(mm)	1500 x 750 x 800(800-830)(mm)	1800 x 750 x 800(800-830)(mm)
INSIDE DIMENSIONS(W x D x H)	830 x 577 x 588(mm)	1130 x 577 x 588(mm)	1430 x 577 x 588(mm)
EFFECTIVE CAPACITY	301 Litre	413 Liter	524 Liter
DEFROST SYSTEM	Glass Tube Heater	Glass Tube Heater	Glass Tube Heater
REFRIGERANT	R134a / 160g	R134a / 150g	R134a / 150g
DOOR / SHELF	DOOR 2 / SHELF 2	DOOR 2 / SHELF 2	DOOR 3 / SHELF 3
PULL DOWN TIME (AT 43°C)	Approx:38min (10°C→0°C)	Approx:22min (10°C→0°C)	Approx:30min (10°C→0°C)
TEMPRETURE CONTROL	- 6 ~ 12°C	- 6 ~ 12°C	- 6 ~ 12°C
EXTERIOR	SUS430 (S) / SUS304 (D,F,T)	SUS430 (S) / SUS304 (D,F,T)	SUS430 (S) / SUS304 (D,F,T)
INTERIOR	SUS430 (S,T) / SUS304 (B)	SUS430 (S,T) / SUS304 (B)	SUS430 (S,T) / SUS304 (B)
DRAIN SYSTEM	WASTE HOSE	WASTE HOSE	WASTE HOSE
OPERATING CONDITIONS	VOLTAGE RANGE	207-254V	207-254V
	AMBIENT TEMP	5 - 43°C	5 - 43°C
PACKAGE (W x D x H)	1265 x 830 x 790(mm)	1565 x 830 x 790(mm)	1865 x 830 x 790(mm)
WEIGHT (NET / GROSS)	85kg / 90kg	102kg / 107kg	117kg / 123kg

●EXTERIOR / INTERIOR : (S) = Side Panel / (D) = Door / (F) = Front Panel / (T) = Top Panel / (B) = Bottom Panel
●Warranty : 1 year parts and labour on entire unit.



HOSHIZAKI

UNDERCOUNTER FREEZER DEPTH 750mm TYPE SERIES



FTC - 120SDA
FTC - 150SDA
FTC - 180SDA

FREEZER
Depth 750mm type

FTC - 180SDA

FTC - 150SDA

FTC - 120SDA

SPECIFICATION

MODEL NAME	FTC-120SDA	FTC-150SDA	FTC-180SDA
AC SUPPLY VOLTAGE	1/220-240V/50Hz	1/220-240V/50Hz	1/220 - 240V/50Hz
AMPERAGE	2.2A	3.2A	3.1A
STARTING AMPERAGE	12.6A	18.6A	18.6A
ELECTRIC CONSUMPTION(Refrigeration)	408W / 1392 BTU	543W / 925 BTU	582W / 1071 BTU
OUTSIDE DIMENSIONS(W x D x H)	1200 x 750 x 800(800-830)(mm)	1500 x 750 x 800(800-830)(mm)	1800 x 750 x 800(800-830)(mm)
INSIDE DIMENSIONS(W x D x H)	830 x 577 x 588(mm)	1130 x 577 x 588(mm)	1430 x 577 x 588(mm)
EFFECTIVE CAPACITY	301 Litre	413 Liter	524 Liter
DEFROST SYSTEM	Glass Tube Heater	Glass Tube Heater	Glass Tube Heater
REFRIGERANT	R404a / 200g	R404a / 190g	R404a / 190g
DOOR / SHELF	DOOR 2 / SHELF 2	DOOR 2 / SHELF 2	DOOR 3 / SHELF 3
PULL DOWN TIME (AT 43°C)	Approx:25min (-5°C→-15°C)	Approx:22min (-5°C→-15°C)	Approx:37min (-5°C→-15°C)
TEMPRETURE CONTROL	- 25 ~ -7°C	- 25 ~ -7°C	- 25 ~ -7°C
EXTERIOR	SUS430 (S) / SUS304 (D,F,T)	SUS430 (S) / SUS304 (D,F,T)	SUS430 (S) / SUS304 (D,F,T)
INTERIOR	SUS430 (S,T) / SUS304 (B)	SUS430 (S,T) / SUS304 (B)	SUS430 (S,T) / SUS304 (B)
DRAIN SYSTEM	WASTE HOSE	WASTE HOSE	WASTE HOSE
OPERATING CONDITIONS	VOLTAGE RANGE	207-254V	207-254V
	AMBIENT TEMP	5 - 43°C	5 - 43°C
PACKAGE (W x D x H)	1265 x 830 x 790(mm)	1565 x 830 x 790(mm)	1865 x 830 x 790(mm)
WEIGHT (NET / GROSS)	91kg / 96kg	105kg / 110kg	120kg / 126kg

●EXTERIOR / INTERIOR : (S) = Side Panel / (D) = Door / (F) = Front Panel / (T) = Top Panel / (B) = Bottom Panel

●Warranty : 1 year parts and labour on entire unit.