

MIWE



MIWE econo Master of Economics

The convection oven for better business at the point of sale.

It sets the stage for baking: Electrically heated convection oven for any capacity requirements with four, six, eight or ten baking tray supports. As the specialist for the convenience sector, it is ideal for all part-baked goods, but also for jams and products like croissants. For even higher throughput, it is also available as a dual circuit model or equipped with a gastronomic function for snack bakers. The perfect stage for sight-and-scent baking.

MIWE econo	EC 4.0604	EC 6.0604	EC 8.0604	EC 10.0604
Number of baking tray supports	4	6	8	8/10
Control system	TC/FP12	TC/FP12	TC/FP12	TC/FP12
Outer dimensions in cm (WxDxH)	90 x 85 x 71	90 x 85 x 87	90 x 85 x 103	90 x 85 x 119
Total weight (without baking trays) kg	155	180	208	232
Connected load kW	6,5	9,4	12,8	15,9
Fuse protection A ¹⁾	3 x 16	3 x 16	3 x 25	3 x 32
Door hinge	Right or left	Right or left	Right or left	Right or left
Steam hood/steam condenser				
Outer dimensions in cm (W x D x H)	90 x 104 x 19	90 x 104 x 19	90 x 104 x 19	90 x 104 x 19
Connected load kW	0,2	0,2	0,2	0,2
Intermediate compartment				
Number of baking tray supports 60 x 40 cm	3/4/6/8	3/4/6/8	3/4/6/8	3/4/6/8
Height cm ²⁾	32	32	32	32
Proofing cabinet				
Number of baking tray supports 60 x 40 cm	10/12/16	10/12/16	10/12/16	10/12/16
Control system	FP3	FP3	FP3	FP3
Height cm ²⁾	54/61/77	54/61/77	54/61/77	54/61/77
Connected load kW	2.2	2.2	2.2	2.2
Fuse protection A ¹⁾	1 x 16	1 x 16	1 x 16	1 x 16
Door hinge	Double door	Double door	Double door	Double door
Base frame				
Number of baking tray supports 60 x 40 cm ³⁾	4/6/10/12/16/20/24	4/6/10/12/16/20/24	4/6/10/12/16/20	4/6/10/12/16/20
Height cm ²⁾	30/54/61/77/93/103	30/54/61/77/93/103	30/54/61/77/93	30/54/61/77/93
Rollers				
Height cm	4 ⁴⁾ /8/11/16	4 ⁴⁾ /8/11/16	4 ⁴⁾ /8/11/16	4 ⁴⁾ /8/11/16

1) Fuse protection at 400/230 V; 3/N/PE; 50 Hz: the fuse protection data is not valid for special voltage!

2) Ground area (W x D) 90 x 85 cm

3) Longitudinal thrust, two-row. Also available for single row as crosswise thrust

4) Not for the proofing cabinet