

MIWE



MIWE aero e+

Top of the class

The convection baking oven for excellent quality throughout the entire product range

Electrically heated universal convection oven for all types of dough pieces. Our best recommendation for shop bakers offering premium quality standards. Equipped with a high-end steam system for the best shine, the ideal bloom and perfect roasting – even when baking frozen dough pieces. For four, six, eight or ten baking tray supports 60 x 40 cm. Also available as a dual circuit model and with gastronomic functions. Its myriad of clever features makes baking a sheer pleasure.

MIWE AERO E+

	AE 4.0604	AE 6.0604	AE 8.0604	EAC10.0604
Number of baking tray supports 60 x 40 cm	4	6	8	8/10
Control system	TC	TC	TC	TC
External dimensions cm (W x D x H)	90 x 85 x 71	90 x 85 x 87	90 x 85 x 103	90 x 85 x 119
Total weight (without trays) kg	163	188	225	249
Connect load kW	8,5	11,4	15,3	19,9
Fuse protection A ¹⁾	3 x 16	3 x 20	3 x 32	3 x 32
Door hand	right or left	right or left	right or left	right or left
Steam hood / steam condenser				
Exterior dimensions cm (WxDxH)	90 x 104 x 19	90 x 104 x 19	90 x 104 x 19	90 x 104 x 19
Connected load kW	0,2	0,2	0,2	0,2
Intermediate compartment				
Number of baking tray supports 60 x 40 cm	3/4/6/8	3/4/6/8	3/4/6/8	3/4/6/8
Height cm ²⁾	32	32	32	32
Proofing cabinet				
Number of baking tray supports 60 x 40 cm	10/12/16	10/12/16	10/12/16	10/12/16
Control system	FP3	FP3	FP3	FP3
Height cm	54/61/77	54/61/77	54/61/77	54/61/77
Connected load kW	2,2	2,2	2,2	2,2
Fuse protection A ¹⁾	1 x 16	1 x 16	1 x 16	1 x 16
Door hand	double door	double door	double door	double door
Under frame				
Number of baking tray supports 60 x 40 cm ³⁾	4/6/10/12/16/20/24	4/6/10/12/16/20/24	4/6/10/12/16/20	4/6/10/12/16/20
Height cm ²⁾	30/54/61/77/93/103	30/54/61/77/93/103	30/54/61/77/93	30/54/61/77/93
Roller				
Height cm	4 ⁴⁾ /8/11/16	4 ⁴⁾ /8/11/16	4 ⁴⁾ /8/11/16	4 ⁴⁾ /8/11/16

1) Fuse protection at 400/230 V; 3/ N/PE; 50 Hz; the fuse protection data is not valid for special voltage!

2) Ground area (W x D) 90 x 85 cm

3) Longitudinal thrust, two-row; also available for single row as crosswise thrust

4) Not for the proofing cabinet

► Accessories: steam hood, modular steam condenser, intermediate compartment, proofing cabinet, underframe, base, rollers, loading system.

► Options: design with black look, MIWE cleaning control, MIWE everclean, triple thermal insulation glazing, energy optimisation connection, restaurant function.