

HONVED ST E



STRONG AND EASY TO USE

- Double panel in finely brushed stainless steel AISI 304
- Hermetic counterbalanced seal door to assure perfect thermoacoustic insulation
- Ergonomic recessed handle



PERFECT HYGIENE

- Self-cleaning internal structure with quick release rinsing nozzles
- Self-cleaning tank filter with extra stainless micro filter (micro-stretched stainless steel) to hold the most persistent dirt



ADVANCED ELECTRONICS

- Digital touch panel control with 4 wash cycles
- Temperatures (washing and rinsing) visualised on the digital display
- Self-diagnostic alarms



HIGH-PERFORMANCE WASH AND RINSE SYSTEM

- Upper and lower wash and rinse arms in stainless steel, adjustable and easy to remove for a better cleaning
- Arms with higher pressure to get a stronger wash action



SAFETY

- Low voltage P.C.B. (12 V)
- Magnetic door micro switch interrupts the cycle if the door is opened accidentally
- The machine stops immediately in the event of low pressure



ACCESSORIES

- Rinse aid pump standard on all models
- Set of standard racks (round or square without adjuster)
- On request:
 - detergent pump kit
 - drain pump kit
 - extra special inclined racks innovative BREAK TANK system (BT – only on ST 48 E and ST 60 E) that allows rinsing at constant temperature and pressure for excellent wash results
- built-in water softener

| | mm 430x530x705 h | mm 480x530x705 h | mm 600x620x826 h |
|-----------------------|--------------------------|--------------------------|--------------------------|
| Model | ST 43 E | ST 48 E | ST 60 E |
| Cycle | 120-180-240-480 sec | 120-180-240-480 sec | 120-180-240-480 sec |
| Wash space | 270 mm | 300 mm | 400 mm |
| Construction | Double wall | Double wall | Double wall |
| Machine interior | Self-cleaning | Self-cleaning | Self-cleaning |
| Rinse aid dispenser | Standard | Standard | Standard |
| Wash pump | 260 W | 700 W | 700 W |
| Detergent pump | Standard | Standard | Standard |
| Rack | 400 x400 mm | 500 x500 mm | 500 x500 mm |
| Electrical connection | Multipower | Multipower | Multipower |
| | 400V 3N50Hz - 230V 50 Hz | 400V 3N50Hz - 230V 50 Hz | 400V 3N50Hz - 230V 50 Hz |
| Total power | 5260 W | 5700 W | 5700 W |
| Boiler heater | 5000 W | 5000 W | 5000 W |
| Tank heater | 2000 W | 1000 W | 1000 W |
| Tank capacity | 12 l | 10 l | 10 l |
| Boiler capacity | 6 l | 8 l | 8 l |
| Water supply | 2÷4 bar Ø 3/4 "G | 2÷4 bar Ø 3/4 "G | 2÷4 bar Ø 3/4 "G |

The hardness of the water supplied must be between 4° and 10° F (French hardness degrees). In case of greater levels of hardness, a water softener must be used.