

# HOONVED

## TL



### STRONG AND EASY TO USE

- Self-supporting structure in finely brushed stainless steel 304
- Double wall door and structure
- Door with hermetic seal for perfect thermo acoustic insulation
- Stainless steel ergonomic recessed handle
- Counterbalanced door



### PERFECT HYGIENE

- Self-cleaning pressed tanks
- Wash arms easy to clean
- Moulded rack support guides to avoid dirt, limescale and detergent buildup
- TL 48: integrated pump and filter with indication if the filter is incorrectly positioned
- TL 60: big wash tank filter and microfilter to collect and convey the dirty directly into the drain, easy to replace and clean with indication if the filter is incorrectly positioned



### ADVANCED ELECTRONICS

- Easy and intuitive soft touch control panel
- Temperatures (wash and rinse) shown on the digital display
- Multifunctional START button with led indicators showing machine status
- 4 wash cycles with adjustable time and temperatures
- Cycle status indicated
- Self-diagnostics via codes to show machine



### INNOVATIVE MPH ARMS FOR WASHING AND RINSING SYSTEM

- Upper and lower wash and rinse stainless steel arms
- New concept of function with combined adjustable arms
- Quick release system
- Removable rinse nozzles



### SAFETY

- Low voltage P.C.B.
- Magnetic door switch interrupts the cycle in case the door is opened accidentally
- Boiler interlock by "dynamic" regulation to ensure the correct rinse temperature



### ACCESSORIES

- Rinse aid pump standard on all models
- Set of standard racks
- On request:
  - extra special inclined racks
  - innovative Break Tank (BT) system that allows the rinse at constant temperature and pressure
  - built-in water softener using reverse osmosis system
  - LPS (Limiter Power System) device to limit the power

	mm 480x530x715 h	mm 600x600x730 h	mm 600x600x830 h
Model	TL 48 - TL 48 BT	TL 60 - TL 60 BT	TL 60A - TL 60A BT
Cycle	120-180-240-480 sec	120-180-240-480 sec	120-180-240-480 sec
Wash space	270 mm	300 mm	400 mm
Construction	Double wall	Double wall	Double wall
Machine interior	Self-cleaning	Self-cleaning	Self-cleaning
Rinse aid pump	Standard	Standard	Standard
Wash pump	260 W	700 W	700 W
Detergent pump	Standard	Standard	Standard
Rack	400 x400 mm*	500 x500 mm	500 x500 mm
Electrical connection	Multipower	Multipower	Multipower
	400V 3N50Hz - 230V 50 Hz	400V 3N50Hz - 230V 50 Hz	400V 3N50Hz - 230V 50 Hz
Total power	5260 W	5700 W	5700 W
Boiler heater	5000 W	5000 W	5000 W
Tank heater	2000 W	1000 W	1000 W
Tank capacity	12 l	10 l	10 l
Boiler capacity	6 l - 4,4 l	8 l - 6,6 l	8 l - 6,6 l
Water supply	2÷4 bar Ø 3/4 "G	2÷4 bar Ø 3/4 "G	2÷4 bar Ø 3/4 "G
Water consumption cycle	2,5 l/ciclo   cycle	2,5 l/ciclo   cycle	2,5 l/ciclo   cycle
Drain hose connection	Ø 28 mm	Ø 31 mm	Ø 31 mm
Acoustic pressure level	< 70 db (A)	< 70 db (A)	< 70 db (A)