

POLIN

SCOOTER 4060



- Outside panels in st/st
- Oven shipped in 2 preassembled elements (fast installation) or completely assembled (as option)
- 9 shelves not removable rack supplied as standard (extractable optional)
- FAST AIR automatic steam exhaust system
- Burner for natural gas or LPG included in the overall dimensions of the oven (SC) (optional)
- Heat generator with armored electric elements (SE)
- Automatic start
- Faceplate/hood without fan
- Double glass door capable of opening up to 160°
- N.3 halogen lamps in the baking chamber
- Electric board included in the overall dimensions of the oven, inside the base (or proofer)
- Integrated air steam condenser (optional)
- Burner or electric elements on the right side (optional)
- Steam generator with liter-counter (optional)
- Base or proof box on wheels

PROOF BOX

- Armored electric element with thermostat for heating
- Water basin with electric element for humidity
- Inner ventilation for even air distribution
- Digital keyboard supplied as standard
- Humidity regulation and control with probe

| | Pan capacity | | Pan size | Minimum door width | Weight | SC Version | | SE Version |
|--------------------------|--------------|-------|----------|--------------------|--------|------------|--------|------------|
| | n° | passo | mm | mm | kg | kW | kcal/h | kW |
| SCOOTER 4060/9 SC | 7 | 115 | 400x600 | 800 | 300 | | 18.000 | - |
| SCOOTER 4060/9 SE | 9 | 90 | 460x600 | (930*) | | 1,4 | - | 15,1** |
| CELL | 14 | 80 | 400x600 | 670 | 80 | | | 2,0 |

* Overall dimensions of the completely assembled oven (930x1440 H=2300 mm)

** With steam generator (18,6 Kw)

The Bakery Equipment Specialist