



BLAST FREEZERS

K-ONE range of blast freezers are the ideal appliance for chefs, pastry chefs and ice cream makers who need reliability and simplicity. They are fitted with a simplified electronic control panel, intuitive and user-friendly, which allows chilling cycles to be set extremely rapidly.

Chilling can be selected by time or according to a probe inserted in the core of the product.

A wide range of products, from small countertop freezers with capacity for three GN 2/3 trays to the spacious freezer with capacity for fifteen GN 1/1 or 40x60 cm trays.



Purchase saving



Reduction in waste



Time saving



Increase in profits



		KBF/03	KBF/05	KBF/05P	KBF/10	KBF/10P	KBF/15	KBF/24
External dimensions (WxDxH)	cm	65x67x67	80x70x90	80x70x90	80x78x170	80x78x170	80x78x200	80x118x200
Trays capacity (trays pitch 67 mm)	nr	3 GN 1/1	5 GN 1/1 5 EN (60x40)	5 GN 1/1 5 EN (60x40)	10 GN 1/1 10 EN (60x40)	10 GN 1/1 10 EN (60x40)	15 GN 1/1 15 EN (60x40)	12 GN 2/1 12 EN (60x80)
Yield*		+90/+3° C = 10 Kg +90/-18° C = 7 Kg	+90/+3° C = 18 Kg +90/-18° C = 11 Kg	+90/+3° C = 26 Kg +90/-18° C = 16 Kg	+90/+3° C = 34 Kg +90/-18° C = 22 Kg	+90/+3° C = 43 Kg +90/-18° C = 32 Kg	+90/+3° C = 50 Kg +90/-18° C = 38 Kg	+90/+3° C = 80 Kg +90/-18° C = 65 Kg
Max absorbed power **	W	975	1185	1430	2010	3720	3820	5320
Refrigerated power ***	W	613	807	1126	1547	2933	2933	5310
Compressor power	Hp	1/2+	1-	1,25	1,5	3	3	3,5
Gas		R452A	R452A	R452A	R452A	R452A	R452A	R452A
Defrosting system		<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Working cycle: by time		●	●	●	●	●	●	●
Working cycle: by probe		○	●	●	●	●	●	●
Input voltage		1x230V - 50Hz	1x230V - 50Hz	1x230V - 50Hz	1x230V - 50Hz	3x400V - 50Hz	3x400V - 50Hz	3x400V - 50Hz

*With ambient temperature of +32° C - load of standard sample of 125 gr. according to DIN 8953/8954

Evap. -10° C cond. +45° C - *ASHRAE (Evap. -23,3° C cond. +54,4° C)

- Automatic with pause
- Automatic with hot gas
- Standard
- On request