

KONE™

PASTRY & GELATO CABINETS



The K-ONE cabinets can accommodate trays measuring 60x40 cm or 60x80 cm; they are equipped with 20 pairs of runners for trays support, in the pastry version, while the gelato version is standard supplied with no. 5 shelves for positioning the gelato bowls.

Made entirely in stainless steel, by respecting the highest possible quality standards, they feature 75mm thick insulation produced by injecting HCFCfree polyurethane resins, with utmost respect for the environment.

They have a radial bottom to enable optimum hygiene and easy cleaning, and a slot-in easy replaceable magnetic seal.

The temperature is controlled by an easy-to-read and programming electronic panel that enables the maximum precision of any working cycle.



Back panel control board



Gelato hardening cycle



Tropicalized system



Thermostatic value system (ARG/40-41)



Radial bottom



Energy save



	KIC/30	KIC/40	KPP/20	KPP/40	KPN/20	KPN/40
External dimensions (WxDxH)	cm 78x90x211	79x108x214	79x69x214	79x108x214	79x69x214	79x108x214
Capacity	Lt 750	900	500	900	500	900
Trays capacity *	nr 54 (5 lt container)	54 (5 lt container)	20 pastry trays 40x60	40 pastry trays 40x60 20 pastry trays 60x80	20 pastry trays 40x60	40 pastry trays 40x60 20 pastry trays 60x80
Standard fittings	nr 5 shelves 56x74	5 shelves 60x80	20 pair of runners	20 pair of runners	20 pair of runners	20 pair of runners
Max absorbed power **	W 880	1200	500	715	795	1200
Refrigerated power W	955***	920***	605**	1005**	650***	920***
Temperature °C	-22/-10	-25/-10	-2/+8	-2/+8	-18/-21	-18/-21
Gas	R452A	R452A	R452A	R452A	R452A	R452A
Input voltage	1x230V/50Hz	1x230V/50Hz	1x230V/50Hz	1x230V/50Hz	1x230V/50Hz	1x230V/50Hz

*Rack with trays pitch 16,5 mm - 36 positions max - **Evap. -10°C cond. +45°C - ***ASHRAE (Evap. -23,3°C cond. +54,4°C)

On request: kit of 4 wheels, extra pair of runners, shelves and trays, glass door with LED lights, special voltage