

## All The Best From **One Supplier**

• SALES • SERVICE • SPARE PARTS •

Perfect hygiene - Easily removable wash and rinse arms for a

perfect cleaning Tank filters and pump suction filters easy to

Versatility - It can be used as a dishwasher with wash capacity of 24 deep plates/26 plates/ 12 pizza plates Ø48cm (+30% compared to a

remove and clean

traditional machine)

# HCONVED C 90 E Dishwasher - Utensil washer / MULTIFUNCTION



## Compact and strong - Small footrprint

- Structure in finely brushed stainless steel 18/10
- Rotating wash and rinse arms in stainless steel - Incoloy stainless stell boiler and heaters

**Safety** - Micro switch interrupts the cycle if the door is opened accidentally

### **Accessories**

- Intergrated rinse-aid pump
- Set of racks for restaurants or, alternatively, for confectionery/ bakery - On request:
- detergent pump
- drain pump
  Break tank (BT) system which allows constant temperature and pressure

슈

- during the rinse phase, ensuring perfect wash results Built-in water softener

| Model                   | CE 68              | CE 78 BT            | C 90 E              |
|-------------------------|--------------------|---------------------|---------------------|
| Dimension               | 660 x 695 x 833 mm | 600 x 695 x 1325 mm | 620 x 742 x 1530 mm |
| H door clearance        | 400 mm             | 400 mm              | 500 mm              |
| Rack                    | 500 x 600 mm       | 500 x 600 mm        | 500 x 600 mm        |
| Construction            | Single wall        | Single wall         | Single wall         |
| Machine interior        | Self-cleaning      | Self-cleaning       | Self-cleaning       |
| Rinse aid-pimp          | Standard           | Standard            | Standard            |
| Wash pump               | 830 W              | 830 W               | 1620 W              |
| Detergent pump          | On request         | On request          | On request          |
| Break Tank system       | 400 V 3N 50Hz      | 400 V 3N 50Hz       | 400 V 3N 50Hz       |
| Electrical connection   | 7830 W             | 7830 W              | 7620 W              |
| Total power             | 7000 W             | 7000 W              | 6000 W              |
| Boiler heater           | 2000 W             | 2000 W              | 3000 W              |
| Tank heater             | 23 L               | 23 L                | 20 L                |
| Tank capacity           | 7.5 L              | 7.5 L               | 8.2 L               |
| Boiler capacity         | 2÷4 bar ø 3/4" G   | 2÷4 bar ø 3/4" G    | 2÷4 bar ø 3/4" G    |
| Water consumption cycle | 3.5 L He bakery L  | 3.5 L               | 4 L                 |
| Drain hose connection   | ø 31 mm            | ø 31 mm             | ø 31 mm             |
| Acoustic pressure level | < 70 db (A)        | < 70 db (A)         | < 70 db (A)         |