

## HOOVED

### CAP Pass-through dishwashers



#### STRONG AND EASY TO USE

- Double wall structure and revolving wash and rinse arms in AISI 304 finely brushed stainless steel
- Double skin tank in finely brushed stainless steel
- Door clearance: 420 mm
- Aligned or corner installation and possibility to integrate tables with sinks
- Counterbalanced hood easy to open



#### PERFECT HYGIENE

- Excellent accessibility inside the machine for easy daily cleaning
- Machine completely rounded inside
- Easy-to-remove stainless steel tank filters
- Suction pump filter to prevent dirt and leftovers from entering and depositing in the wash circuit



#### ADVANCED ELECTRONICS

- Keyboard with digital display of wash and rinse temperatures
- 4 wash cycles (short-medium-long-intensive)
- Cycle stop with led displayed alarm
- Possibility to set the automatic washing by closing the door
- Backlit controls
- On models CAP 10-12 E, it is possible to personalize the wash and the rinse phase



#### ACCESSORIES

- Standard supply rinse aid pump
- Standard supply racks on every machine
- On request:
  - detergent pump and drain pump
  - condensing unit
  - heat pump
  - thermal-acoustic insulation
  - insulation
  - external shower
  - wheels
- BREAK TANK (BT) system on CAP 10 and 12 only. This exclusive technology:
  - assures constant temperature and pressure during the rinse phase
  - prevents the washing cycles without water
  - prevents boiler water backflow towards the water supply
  - prevents any contamination of the water in the mains
- includes standard rinse booster pump
- not available on model CAP 7



#### SAFETY

- Low voltage electronic control (12 V)
- Keyboard and display panel splash-proof (protection IP53)
- Cycle-stop microswitch in case of accidental door opening

	mm 625/740x1470h/1960 h	mm 625x740x1470h/1960 h	mm 625x740x1470h/1960 h
Model	CAP 7 E (M.P.H. - M.L.R.)	CAP 10 E	CAP 12 E
Cycle length	120-180-240 sec - Max 8 min	65/100/150 sec - Max 8 min	55/85/120 sec - Max 8 min
Wash space	500 x 500 x 420 h mm	500 x 500 x 420 h mm	500 x 500 x 420 h mm
Construction	Double wall	Double wall	Double wall
Machine interior	Self-cleaning	Self-cleaning	Self-cleaning
Rinse-aid dispenser	Standard	Standard	Standard
Wash pump	750 W	1100 W	1620 W
Dishes/h	540/720	1000	1200
Detergent pump	On request	On request	On request
Break tank system	-	Optional	Optional
Electrical connection	400 V 3N ~ 50 Hz	400 V 3N ~ 50 Hz	400 V 3N ~ 50 Hz
Total Power	6750 W	7100 W	11620 W
Boiler heater	6000 W	6000 W	10000 W
Tank heater	4000 W	4000 W	4000 W
Tank capacity	42 l	42 l	42 l
Boiler capacity	8,2 l	8,2 l	8,2 l
Water supply	2÷4 bar Ø 3/4 "G	2÷4 bar Ø 3/4 "G	2÷4 bar Ø 3/4 "G
Water consumption cycle	3,5 l	3,5 l	3,5 l
Drain hose connection	Ø 1 "G	Ø 1 "G	Ø 1 "G
Acoustic pressure level	< 70 db (A)	< 70 db (A)	< 70 db (A)