

HOOONVED TLC Top Line Hood type dishwashers



STRONG AND EASY TO USE

- Structure and revolving wash and rinse arms in AISI 304 finely brushed stainless steel
- Double skin tank in finely brushed stainless steel
- Door clearance: 420 mm – 500 mm
- Lineal or corner installation and possibility to integrate tables with sink
- Counterbalanced hood easy to open



SAFETY

- Low voltage electronic control (12 V).
- Keyboard and display panel splash-proof (protection IP53)
- Cycle-stop microswitch in case of accidental door opening
- Boiler interlock by "dynamic" regulation to ensure the correct rinse temperature



ADVANCED ELECTRONICS

- Same electronic of TL line
- Soft Start Keyboard on the top with digital display of wash and rinse temperatures
- 4 wash cycles + ECO2 cycle
- Cycle stop with led displayed alarm
- Possibility to set the automatic washing by closing the door
- Backlight controls
- Possibility to personalize the wash and the rinse phase



ACCESSORIES

- Rinse-aid dispenser, detergent pump and rinse aid pump standard
- Break Tank standard
 - assures constant temperature and pressure during the rinse phase
 - prevents the washing cycles without water
 - prevents boiler water backflow towards the water supply
 - prevents any contamination of the water in the mains
- includes standard rinse booster pump
- Set of racks included in every machine
- On request:
 - detergent pump and drain pump
 - condensing unit
 - heat pump
 - thermal-acoustic insulation
 - insulation
 - external shower
 - wheels



PERFECT HYGIENE

- Interior of the machine completely rounded for easy cleaning action
- Big wash tank filter and microfilter to collect and convey the dirty directly into the drain, easy to replace and clean with indication if the filter is incorrectly positioned
- Suction pump filter to protect the wash pump and prevent leftovers from depositing in the wash circuit
- Excellent accessibility inside the machine for easy daily cleaning

Model	mm 625/740x1525h/2040 h TLC 100	mm 725x740x1625h/2195 h TLC 150
Cycle length	63-88-118-238 sec	46-88-118-238 sec
Wash space	415 mm	500 mm
Construction	Double wall	Double wall
Machine interior	Self-cleaning	Self-cleaning
Rinse-aid dispenser	Standard	Standard
Wash pump	1100 W	2200 W
Dishes/h	1000	1450
Detergent pump	Standard	Standard
Break tank system	Standard	Standard
Electrical connection	230V/3/50Hz; 400V/3N/50Hz	230V/3/50Hz; 400V/3N/50Hz
Total Power	10100 W	11200 W
Boiler heater	9000 W	9000 W
Tank heater	3000 W	3000 W
Tank capacity	42 l	42 l
Boiler capacity	8,2 l	8,2 l
Water supply	2÷4 bar Ø 3/4 "G	2÷4 bar Ø 3/4 "G
Water consumption cycle	3,5 l	3,5 l
Drain hose connection	Ø 1 "G	Ø 1 "G
Acoustic pressure level	< 70 db (A)	< 70 db (A)
RCC condensing unit	On request	On request