

All The Best From **One Supplier**

• SALES • SERVICE • SPARE PARTS •

ASM EVO SPIRAL MIXER WITH FIXED BOWL

STANDARD FEATURES

- Painted steel structure raised from the ground on 4 adjustable feet.
- Bowl, spiral, contrast column and guard made in stainless steel.
- Two independent 2-speed motors for spiral and bowl.
- Movement is trasmitted by pulleys and V-belts.
- Bowl thrust roller.
- Frontal control with two timers.
- Setting of work time with automatic shift from 1st to 2nd speed.
- Selector to reverse bowl.
- Impulse button to rotate bowl for product removal.
- Selector to activate second bowl speed.

CAPACITY (kg) •60 •80 •100 •130 •160

•200 •250

TECHNICAL DATA

MODEL			ASM EVO 60	ASM EVO 80	ASM EVO 100	ASM EVO 130	ASM EVO 160	ASM EVO 200	ASM EVO 250
Dough capacity (min./max) *	J.C.	kg	5/60	8/80	8/100	10/130	10/160	10/200	15/250
Flour capacity (min./max) *		kg	3/38	5/50	5/62	6/80	6/100	6/125	9/150
Water capacity (min./max) *		lt	2/22	3/30	3/38	4/50	4/60	4/75	6/100
Bowl volume		lt	100	135	155	205	260	285	380
% water/flour minimum		%	50	50	50	50	50	50	50
Spiral turns 1st /2nd speed (50/60hz)		rpm	93/184	98/194	98/194	98/194	92/182	92/182	92/183
Bowl turns 1st / 2nd speed (50/60Hz)		rpm	10.5/21	10/20	10/20	9.5/19	9/18	9/18	9/18
Motor power 1st speed		kw	2.35	2.9	2.9	3.6	4.6	4.6	5.4
Motor power 2nd speed		kw	3.15	5.3	5.3	6.3	7.4	7.4	8.6
Current drawn V 230		А	12	20.5	20.5	23.5	34	34	34
Current drawn V 400		А	7.5	12	12	13.5	17.5	17.5	20.5
Spiral bar diameter		mm	30	35	35	40	48	48	60
Height from bowl edge	A	mm	890	890	890	950	910	940	975
Total depth	P	mm	1040	1190	1190	1275	1460	1460	1565
Total width	L	mm	635 BA	745	745	lict 845	945	945	1045
Total height	Н	mm	1360	1415	1415	1470	1500	1500	1500
Net weight	182	kg	300	390	395	460	650	650	670

*: capacity based on the percentage of liquid/flour = 60%

All data are to be considered as nominal, MIXER srl reserves the right to make any changes to the product and/or technical specifications without notice.



