

HOONVED HPW

Double-skin utensil washers with Wi-Fi connection and remote control



ADVANCED ELECTRONICS

- Digital touch panel control with 4 wash cycles
- Temperatures (washing and rinsing) visualised on the digital display
- Self-diagnostic alarms



STRONG AND EASY TO USE

- Double wall structure in AISI 304 stainless steel
- Revolving wash and rinse arms in AISI 304 stainless steel
- Easy-to-open counterbalanced split door
- Side control panel
- Superior Clearance
- Ergonomics



WI-FI CONNECTION

- Control and monitoring of unit's consumptions and activity status
- Modification of parameters and remote anomalies resolution by the technician
- Constant performance and optimization of water, energy and detergent consumption.
- Reduction in on-site technical interventions up to 50%.
- Possibility for the technician to plan preventive maintenance intervention



SAFETY

- Easy access to the technical compartment thanks to the full-length lower panel.
- Inner unit's components are organized in the technical compartment in such a way as to offer the technician the possibility of an overall first diagnosis, without need to move the machine.
- Easily removable full-height side uprights



PERFECT HYGIENE

- Excellent accessibility inside the machine for easy daily cleaning
- Machine completely rounded inside
- Easy-to-remove stainless steel tank filters
- Suction pump filter to prevent dirt and leftovers from entering and depositing in the wash circuit



INNOVATION

- BREAK TANK System (BT) standard on all the models. This exclusive technology:
- ensures that rinsing occurs at a constant pressure and temperature
 - prevents washing cycles without water
 - prevents boiler water backflow towards the mains water supply
 - prevents any contamination of the mains water supply
 - includes standard rinse booster pump



SAFETY

- Low voltage P.C.B. (12 V)
- Keyboard and display panel IP53 splashguard protection
- Micro switch interrupts the cycle if the door is opened accidentally



ACCESSORIES

- Standard supply detergent pump & rinse aid pump
- Standard supply racks on every machine
- On request:
 - external shower
 - wheels
 - drain pump
 - heat recovery unit
 - heat pump
 - thermal-acoustic insulation

Femac

Model	HPW 40BT	HPW 60BT	HPW 80BT	HPW 130BT
Cycle length	120/240/360/480 sec	120/240/360/480 sec	120/240/360/480 sec	120/240/360/480 sec
Clearance	670 mm/ 820 mm*	670 mm/ 820 mm*	670 mm/ 820 mm*	670 mm/ 820 mm*
Construction	550 x 650 mm	650 x 700 mm	810 x 700 mm	1320 x 700 mm
Dimension	720 x 858 x 1712/1862*h mm	836 x 915 x 1890/2040*h mm	996 x 915 x 1890/2040*h mm	1506 x 915 x 1890/2040*h mm
Machine interior	Self-cleaning	Self-cleaning	Self-cleaning	Self-cleaning
Wash pump	On request	On request	On request	On request
Detergent pump	On request	On request	On request	On request
Break tank system	Standard	Standard	Standard	Standard
Electrical connection	400V 3N 50Hz	400V 3N 50Hz	400V 3N 50Hz	400V 3N 50Hz
Total power	7500W	9000W	9000W	15000W
Boiler heater	6000W	6000W	6000W	9000W
Tank heater	4000W	6000W	6000W	9000W
Tank capacity	42 l	82 l	86 l	132 l
Boiler capacity	10,5	14,5	14,5	14,5
Water supply	2÷4 bar ø 3/4" G	2÷4 bar ø 3/4" G	2÷4 bar ø 3/4" G	2÷4 bar ø 3/4" G
Water consumption cycle	4,5 l	4,5 l	5 l	8 l